


ENTRY PLUGS - POLYAMIDE PA6

Metric thread M 1.5 pitch CEI EN 60423

Ref. Light Grey	P	Ø A (mm)	C (mm)	Quantity
1053M12	M12X1,5	15	6	100
1053M16	M16X1,5	20	6	100
1053M20	M20X1,5	25	7	100
1053M25	M25X1,5	30	7	100
1053M32	M32X1,5	37	9	50
1053M40	M40X1,5	47	9	30
1053M50	M50X1,5	58	10	20
1053M63	M63X1,5	72	12	10

Add to Ref: N for Black

Pg thread DIN 40 430 - Dimensions DIN 46 320

Ref. Light Grey	P	Ø A (mm)	C (mm)	Quantity Box/Bag
1052007	Pg 7	15	6	100
1052009	Pg 9	19	6	100
1052011	Pg11	22	7	100
1052013	Pg13,5	25	7	100
1052016	Pg16	27	7	100
1052021	Pg21	33	9	50
1052029	Pg29	44	9	100/50
1052036	Pg36	55	10	20
1052042	Pg42	62	10	10
1052048	Pg48	69	12	10

Add to Ref: N for Black

Technical details:

PROTECTION :	IP 54 (EN 60529:1991 / CEI 70-1)
MATERIAL :	POLYAMIDE 6
SELF-EXTINGUISHING CLASS :	V0 (UL 94)
TEMPERATURE RANGE :	-20°C ÷ +90°C (continuous) -20°C ÷ +110°C (short period)
COLOUR :	RAL 7035 light grey, RAL 9005 black,

Resistance to chemical:	<i>STRONG ACIDS - not resistant</i>
	<i>SOFT ALKALINES - not resistant</i>
	<i>STRONG ALKALINES - not resistant</i>
	<i>IDROCARBONS - resistant</i>
	<i>CHLORIDES - not resistant</i>
	<i>ALCOHOLS - resistant</i>
	<i>KETONES - resistant</i>

Cembre SpA

Via Serenissima, 9 - 25135 Brescia (Italy)
 Tel.: +39 030 36921 - Fax: +39 030 3365766
 Web: www.cembre.com - Email: info@cembre.com