

CUTTING CAPACITY

Material		Tensile strength (daN/mm ²)	Max cutting diameter (mm) B-TC550
ROPES & CONDUCTORS	COPPER	≤ 41	55
	ALUMINIUM	≤ 20	55
	ALMELEC	≤ 34	55
	STEEL	≤ 180	INDICATIVE EXAMPLES: 7 x 3,0 : Ø est. = 9,0 mm 19 x 2,1 : Ø est. = 10,5 mm 19 x 2,3 : Ø est. = 11,5 mm
	MULTI STRANDS STEEL (STRANDS Qty ≥ 200)	≤ 180	22
	ACSR	≤ 180	50 INDICATIVE EXAMPLES: 26 x 2,50 + 7 x 1,95 : Ø est. = 15,85 26 x 3,06 + 7 x 2,38 : Ø est. = 19,38 26 x 3,60 + 7 x 2,80 : Ø est. = 22,80 26 x 4,44 + 7 x 3,45 : Ø est. = 28,14 54 x 3,50 + 19 x 2,10 : Ø est. = 31,50 54 x 4,36 + 19 x 2,62 : Ø est. = 39,20 83 x 4,60 + 16 x 2,80 : Ø est. = 50,00
	GUY WIRE (GW15-9/16-188)	Extra high strenght grade	7 x 4,77 : Ø est. =14,30 mm
	STEEL	≤ 60 ≤ 42	20 22
	COPPER	≤ 30 ≤ 25	34 38,5
	ALUMINIUM	≤ 16	50
RODS			