## Part number CX 02 CHF

Further technical details

Insulation resistance

Contact resistance UL 94 flammability rating

Weight

Characteristics according to 16A 2500V 15kV 3 EN 61984

 $\geq 10 \; G\Omega \\ \leq 1 \; m\Omega$ 

V-0 28,50 g





## Brief description:


female insert, 2 poles, crimp connection, 16A, 2500V, 1 module, modular units MIXO series


Product description		General ordering information	
Model	female insert	EAN13 code	8015747203104
Version	Crimp connection	Packaging Information	
Product type	for female contacts 16A	Sub-packaging weight	0,03 kg
Family	MIXO series, customizable inserts	Sub-packaging description	Plastic bag
Size	1 module	Sub-packaging quantity	1 Pcs
N. of poles	2 poles	Sub-packaging EAN barcode	8015747203111
Technical data			
Current	16 A (A.C. and D.C.)		
Voltage	2500 V		
Rated impulse withstand voltage	15kV		
Pollution degree	3		
Operating temperature range (min, max)	-40 °C +125 °C		
Contacts material	silver plated, gold plated		
Mating cycles	≥ 500		
IP degree of protection	IP20 without enclosure; IP65/IP66/IP67/IP68 with enclosure		

## Part number CX 02 CHF



Catalogue drawings






Μ

F

Γ




contacts side (front view)

side with reference arrow  $\blacktriangle$ 

F





Μ

- 1 frame slot

## Notes

the modular inserts must be installed in suitable frames which in turn are installed in traditional housings or COB panel support