


Part number

CX 01 BM



Brief description:

male insert, 1 pole + shield, shielded connectors, 10A 50V, 0,8kV, 3, modular units series MIXO

Product description		Approvals / Standards	
Model	male insert	Reference standard	EN 61984:2009-06
Version	shielded connectors	Quality mark	 , DNV GL
Product type	for male contacts 10A	Conformity	CQC
Style	one contacts seat + shield	General ordering information	
Family	MIXO series, customizable inserts	EAN13 code	8015747137232
N. of poles	1 pole + shield	Tariff number	85369095
Technical data		Packaging Information	
Current	10 A (A.C. and D.C.)	Packaging weight	0,25 kg
Voltage	50 V	Packaging description	Carton box
Rated impulse withstand voltage	0,8kV	Packaging quantity	10 Pcs
Pollution degree	3	Packaging EAN code	8015747137294
Operating temperature range (min, max)	-40°C ... +70°C	Sub-packaging length	105,00 mm
IP degree of protection	IP20 without enclosure, IP65/IP66/IP68/IP69 with enclosure	Sub-packaging height	70,00 mm
Further technical details		Sub-packaging width	110,00 mm
Characteristics according to EN 61984	10A 50V 0.8kV 3	Sub-packaging weight	0,03 kg
Insulation resistance	≥ 10 GΩ	Sub-packaging volume	0,81 dm ³
Rated voltage according to UL/CSA	600V	Sub-packaging description	Plastic bag
UL 94 flammability rating	V-0	Sub-packaging quantity	1 Pcs
Weight	25,00 g	Sub-packaging EAN barcode	8015747137300


Part number

CX 01 BM




Catalogue drawings

CX 01 BF



CX 01 BM



Notes

CX 01 B inserts:

- characteristics according to EN 61984:
(10A 50V 0,8kV 3)

the modular inserts must be installed in suitable frames which in turn are installed in traditional housings or COB panel support
