

# Part number

# CKSF 03



## Brief description:

female insert, 3 poles + PE, spring terminal connections , 10A, 400V, 4kV, 3, silver plated, size "21.21", CLASS insert series



Product description		Approvals / Standards	
<b>Model</b>	female insert	<b>Reference standard</b>	EN 61984:2009-06
<b>Version</b>	spring terminal connections	<b>Quality mark</b>	DNV-GL, EAC
<b>Series</b>	CKS	<b>Conformity</b>	CQC, CE
<b>Product type</b>	with female contacts	General ordering information	
<b>Family</b>	CLASS inserts	<b>EAN13 code</b>	8015747164399
<b>Size</b>	size "21.21"	<b>Tariff number</b>	85369095
<b>N. of poles</b>	3 poles +	<b>Country of origin</b>	Made in EU (IT)
Technical data		<b>ETIM classification</b>	EC000438
<b>Current</b>	10 A (A.C. and D.C.)	Packaging Information	
<b>Voltage</b>	400 V	<b>Packaging length</b>	210,00 mm
<b>Rated impulse withstand voltage</b>	4kV	<b>Packaging height</b>	200,00 mm
<b>Pollution degree</b>	3	<b>Packaging width</b>	130,00 mm
<b>Wire cross-section</b>	0,14 mm <sup>2</sup> - 2,50 mm <sup>2</sup>	<b>Packaging weight</b>	3,18 kg
<b>AWG size</b>	26 - 14	<b>Packaging volume</b>	5,46 dm <sup>3</sup>
<b>Operating temperature range (min, max)</b>	-40°C ... +125°C	<b>Packaging description</b>	Carton box
<b>Contacts material</b>	Brass	<b>Packaging quantity</b>	200 Pcs
<b>Contact type</b>	silver plated	<b>Packaging EAN code</b>	8015747164474
<b>Mating cycles</b>	≥ 500	<b>Sub-packaging weight</b>	0,64 kg
<b>IP degree of protection</b>	IP20 without enclosure, IP44/IP66/IP67/IP68/IP69 with enclosure	<b>Sub-packaging description</b>	Carton tray
<b>PE connection type</b>	Spring	<b>Sub-packaging quantity</b>	40 Pcs
<b>PE terminal stripping length</b>	9...11 mm	<b>Sub-packaging EAN barcode</b>	8015747164481
<b>Tightening torque for PE connection</b>	M4: 1,2 Nm, 10,6 lb.in (Ph2 or 1,0x5,5mm )		
Further technical details			
<b>Characteristics according to EN 61984</b>	10A 400V 4kV 3; 10A 690V 4kV 2		
<b>Insulation resistance</b>	≥ 10 GΩ		
<b>Contact resistance</b>	≤ 3 mΩ		
<b>Rated voltage according to UL/CSA</b>	600V		
<b>UL 94 flammability rating</b>	V-0		
<b>Main contacts stripping length</b>	9...11 mm		
<b>Torque for main contact</b>	M2,5: 0.4 Nm; 3.5 lb.in (0,5 x 3mm )		
<b>Tightening torque for fixing screws</b>	M3: 0.5 Nm; 4.4 lb.in (0.5x3 mm)		
<b>Weight</b>	15,00 g		

Part number


# CKSF 03



Catalogue drawings




Catalogue drawings



## Notes

Spring terminal connections



Rear top entry of wires for a more easier wiring.

---