

Part number

C7I 06 L



Brief description:

bulkhead mounting housings with single lever, size "44.27", metal version, IP66/ IP67

Product description

Version	C7 - CV and M7 - MV enclosures, V-Type lever version
Series	Bulkhead mounting housings with 1 lever
Product type	with stainless steel lever
Family	C7 - CV and M7 - MV enclosures, V-Type lever version
Size	size "44.27"



Technical data

Operating temperature range (min, max)	-40 °C...+125 °C
Material	metal
IP degree of protection	IP66/ IP67 (EN 60529) and IP69K (DIN 40050 - 9) degree of protection.

Further technical details

Weight	93,00 g
---------------	---------

Approvals / Standards

Quality mark	 (type:4/4X/12),  , EAC
Conformity	CQC, CE

General ordering information

EAN13 code	8015747093613
Tariff number	85369095

Packaging Information

Packaging length	175,00 mm
Packaging height	195,00 mm
Packaging width	260,00 mm
Packaging weight	4,02 kg
Packaging volume	8,87 dm ³
Packaging description	Carton box
Packaging quantity	40 Pcs
Packaging EAN code	8015747178099
Sub-packaging weight	0,50 kg
Sub-packaging description	Plastic packaging
Sub-packaging quantity	5 Pcs
Sub-packaging EAN barcode	8015747178105


Part number

C71 06 L




Catalogue drawings

C71 L



	A	B
C71 06 L	66	82,5

Catalogue drawings



Notes

C71:

Due to the vertical closing movement, the new lever offers an IP66/IP67 protection (according to EN 60529) when fitted with a complete and coupled connector and used with ILME standard hoods in die cast aluminum with pegs (without adaptor).

For bulkhead-mounting housings, the IP66/IP67 protection class is guaranteed if the housings are fitted on sufficiently rigid panels, M4 screws of suitable length (negligible bending of the surface when exposed to the tightening torque of 0.8-1.2Nm of the fixing screws or to the deformations caused by the actual weight of the complete connector).

If rigidity is insufficient, is advisable to use CG .. FL flanges, M4 screws of suitable length and M4 flat/elastic washers (for the housing side) and M6 flat/elastic washers (for the flange side) with M4 locking nuts.

It is also important to check that the panel in contact with the gasket of the bulkhead-mounting housing flange is free from imperfections (deep scratches, grooves, burs) that could affect the operation of the gasket.