


# AVA6RK-50



AVA6-50, HELIAX® Andrew Virtual Air™ Coaxial Cable, corrugated copper, 1-1/4 in, black, fire retardant polyolefin jacket B2ca- s1b, d2,a1 (CPR testing is conducted annually please reference the website for latest classification)

## Product Classification

|                       |                        |
|-----------------------|------------------------|
| <b>Brand</b>          | HELIAX®                |
| <b>Product Series</b> | AVA6-50                |
| <b>Product Type</b>   | Coaxial wireless cable |

## Standards And Qualifications

|                                    |                      |
|------------------------------------|----------------------|
| <b>EN50575 CPR Cable EuroClass</b> | B2ca   s1b   d2   a1 |
|------------------------------------|----------------------|

## Construction Materials

|                                 |  |
|---------------------------------|--|
| <b>Jacket Material</b>          | Non-halogenated, fire retardant polyolefin |
| <b>Outer Conductor Material</b> | Corrugated copper                          |
| <b>Dielectric Material</b>      | Foam PE                                    |
| <b>Flexibility</b>              | Standard                                   |
| <b>Inner Conductor Material</b> | Corrugated copper tube                     |
| <b>Jacket Color</b>             | Black                                      |

## Dimensions

|                                 |                        |
|---------------------------------|------------------------|
| <b>Nominal Size</b>             | 1-1/4 in               |
| <b>Cable Weight</b>             | 0.54 lb/ft   0.80 kg/m |
| <b>Diameter Over Dielectric</b> | 34.036 mm   1.340 in   |
| <b>Diameter Over Jacket</b>     | 39.624 mm   1.560 in   |
| <b>Inner Conductor OD</b>       | 14.0208 mm   0.5520 in |
| <b>Outer Conductor OD</b>       | 36.068 mm   1.420 in   |

## Electrical Specifications

|                                       |                                |
|---------------------------------------|--------------------------------|
| <b>Cable Impedance</b>                | 50 ohm ±1 ohm                  |
| <b>Capacitance</b>                    | 22.0 pF/ft   72.0 pF/m         |
| <b>dc Resistance, Inner Conductor</b> | 0.530 ohms/kft   1.740 ohms/km |
| <b>dc Resistance, Outer Conductor</b> | 0.230 ohms/kft   0.750 ohms/km |
| <b>dc Test Voltage</b>                | 8500 V                         |

# AVA6RK-50

---

|  |                                    |
|--|------------------------------------|
| <b>Inductance</b>                      | 0.057 $\mu$ H/ft   0.187 $\mu$ H/m |
| <b>Insulation Resistance</b>           | 100000 Mohms•km                    |
| <b>Jacket Spark Test Voltage (rms)</b> | 10000 V                            |
| <b>Operating Frequency Band</b>        | 1 – 3700 MHz                       |
| <b>Peak Power</b>                      | 180.0 kW                           |
| <b>Velocity</b>                        | 92 %                               |

## Environmental Specifications

|                                 |                                      |
|---------------------------------|--------------------------------------|
| <b>Installation Temperature</b> | -40 °C to +60 °C (-40 °F to +140 °F) |
| <b>Operating Temperature</b>    | -40 °C to +60 °C (-40 °F to +140 °F) |
| <b>Storage Temperature</b>      | -40 °C to +60 °C (-40 °F to +140 °F) |

## General Specifications

|                      |  |
|----------------------|--|
| <b>Ordering Note</b> | CommScope® standard product in Europe, the Middle East, and Africa |
|----------------------|--|

## Mechanical Specifications

|  |                               |
|--|-------------------------------|
| <b>Bending Moment</b>                      | 29.8 N-m   22.0 ft lb         |
| <b>Fire Retardancy Test Method</b>         | NFPA 130-2010   UL 1666/CATVR |
| <b>Flat Plate Crush Strength</b>           | 75.0 lb/in   1.3 kg/mm        |
| <b>Minimum Bend Radius, Multiple Bends</b> | 203.20 mm   8.00 in           |
| <b>Minimum Bend Radius, Single Bend</b>    | 152.40 mm   6.00 in           |
| <b>Number of Bends, minimum</b>            | 15                            |
| <b>Number of Bends, typical</b>            | 40                            |
| <b>Smoke Index Test Method</b>             | IEC 61034                     |
| <b>Tensile Strength</b>                    | 154 kg   340 lb               |
| <b>Toxicity Index Test Method</b>          | IEC 60754-1   IEC 60754-2     |

## Note

|                         |   |
|-------------------------|---|
| <b>Performance Note</b> | Values typical, unless otherwise stated |
|-------------------------|---|

## Standard Conditions

|   |                 |
|---|-----------------|
| <b>Attenuation, Ambient Temperature</b>           | 68 °F   20 °C   |
| <b>Average Power, Ambient Temperature</b>         | 104 °F   40 °C  |
| <b>Average Power, Inner Conductor Temperature</b> | 212 °F   100 °C |

## Return Loss/VSWR

| <b>Frequency Band</b> | <b>VSWR</b> | <b>Return Loss (dB)</b> |
|-----------------------|-------------|-------------------------|
| 680–800 MHz           | 1.13        | 24.30                   |

# AVA6RK-50

---

|               |      |       |
|---------------|------|-------|
| 806–960 MHz   | 1.13 | 24.30 |
| 1700–2170 MHz | 1.13 | 24.30 |

## Attenuation

| Frequency (MHz) | Attenuation (dB/100 m) | Attenuation (dB/100 ft) | Average Power (kW) |
|-----------------|------------------------|-------------------------|--------------------|
| 0.5             | 0.056                  | 0.017                   | 117.01             |
| 1               | 0.079                  | 0.024                   | 82.63              |
| 1.5             | 0.097                  | 0.03                    | 67.41              |
| 2               | 0.113                  | 0.034                   | 58.33              |
| 10              | 0.253                  | 0.077                   | 25.89              |
| 20              | 0.36                   | 0.11                    | 18.21              |
| 30              | 0.443                  | 0.135                   | 14.80              |
| 50              | 0.576                  | 0.176                   | 11.39              |
| 85              | 0.758                  | 0.231                   | 8.66               |
| 88              | 0.772                  | 0.235                   | 8.51               |
| 100             | 0.825                  | 0.251                   | 7.96               |
| 108             | 0.858                  | 0.262                   | 7.65               |
| 150             | 1.019                  | 0.311                   | 6.44               |
| 174             | 1.102                  | 0.336                   | 5.96               |
| 200             | 1.186                  | 0.361                   | 5.53               |
| 204             | 1.198                  | 0.365                   | 5.48               |
| 300             | 1.471                  | 0.448                   | 4.46               |
| 400             | 1.717                  | 0.523                   | 3.82               |
| 450             | 1.829                  | 0.558                   | 3.59               |
| 460             | 1.851                  | 0.564                   | 3.54               |
| 460             | 1.851                  | 0.564                   | 3.54               |
| 500             | 1.937                  | 0.59                    | 3.39               |
| 512             | 1.962                  | 0.598                   | 3.34               |
| 600             | 2.14                   | 0.652                   | 3.07               |
| 700             | 2.329                  | 0.71                    | 2.82               |
| 800             | 2.507                  | 0.764                   | 2.62               |
| 824             | 2.548                  | 0.777                   | 2.58               |
| 894             | 2.666                  | 0.813                   | 2.46               |
| 960             | 2.774                  | 0.846                   | 2.37               |
| 1000            | 2.838                  | 0.865                   | 2.31               |
| 1218            | 3.171                  | 0.967                   | 2.07               |
| 1250            | 3.218                  | 0.981                   | 2.04               |
| 1500            | 3.569                  | 1.088                   | 1.84               |
| 1700            | 3.835                  | 1.169                   | 1.71               |
| 1794            | 3.955                  | 1.206                   | 1.66               |
| 1800            | 3.963                  | 1.208                   | 1.66               |
| 2000            | 4.212                  | 1.284                   | 1.56               |
| 2100            | 4.333                  | 1.321                   | 1.51               |
| 2200            | 4.452                  | 1.357                   | 1.47               |
| 2300            | 4.569                  | 1.393                   | 1.44               |
| 2500            | 4.798                  | 1.463                   | 1.37               |
| 2700            | 5.021                  | 1.53                    | 1.31               |
| 3000            | 5.345                  | 1.629                   | 1.23               |
| 3400            | 5.76                   | 1.755                   | 1.14               |
| 3600            | 5.961                  | 1.817                   | 1.10               |

# AVA6RK-50

---

3700

6.06

1.847

1.08

\* Values typical, guaranteed within 5%

## Regulatory Compliance/Certifications

### Agency

UL/ETL Certification

RoHS 2011/65/EU

ISO 9001:2015

China RoHS SJ/T 11364-2014

CENELEC

### Classification

Compliant

Compliant

Designed, manufactured and/or distributed under this quality management system

Below Maximum Concentration Value (MCV)

EN 50575 compliant, Declaration of Performance (DoP) available



CENELEC