


Part number

# CX 36 IM



male modular insert, Mixo series, crimp connection, 36 poles, 1 module, 4 A 32 V 0,8 kV 3


Product description		Material properties	
<b>Product type</b>	modular insert	<b>Main material</b>	polycarbonate
<b>Series</b>	Mixo	<b>Colour</b>	RAL 7032 grey
<b>Connection type</b>	crimp connection	<b>General ordering information</b>	
<b>Gender</b>	male	<b>EAN13 code</b>	8015747270106
<b>N. of poles</b>	36 poles	<b>Packaging Information</b>	
<b>Size</b>	1 module	<b>Packaging length</b>	180,00 mm
<b>Technical data</b>		<b>Packaging height</b>	130,00 mm
<b>Current</b>	4 A	<b>Packaging width</b>	150,00 mm
<b>Voltage</b>	32 V	<b>Packaging weight</b>	5,93 kg
<b>Rated impulse withstand voltage</b>	0,8 kV	<b>Packaging volume</b>	3,51 dm <sup>3</sup>
<b>Pollution degree</b>	3	<b>Packaging description</b>	Carton box
<b>Rated voltage according to UL/CSA</b>	30 V	<b>Packaging quantity</b>	60 Pcs
<b>IP degree of protection</b>	IP20 without enclosure, IP65/IP66/IP68/IP69 with enclosure	<b>Packaging EAN code</b>	8015747270137
<b>Further technical details</b>		<b>Sub-packaging length</b>	35,00 mm
<b>Characteristics according to EN 61984</b>	4 A 32 V 0,8 kV 3	<b>Sub-packaging height</b>	40,00 mm
<b>Mating cycles</b>	≥ 500	<b>Sub-packaging width</b>	155,00 mm
<b>Insulation resistance</b>	≥ 10 GΩ	<b>Sub-packaging weight</b>	0,99 kg
<b>Weight</b>	7,00 g	<b>Sub-packaging volume</b>	0,22 dm <sup>3</sup>
<b>Operating temperature range (min, max)</b>	-40 °C ... +125 °C	<b>Sub-packaging description</b>	Carton tray
<b>UL 94 flammability rating</b>	V-0	<b>Sub-packaging quantity</b>	10 Pcs
		<b>Sub-packaging EAN barcode</b>	8015747270144

Part number

# CX 36 IM



## Catalogue drawings



---

## Notes

Dimensions shown in mm are not binding and may be changed without notice.

---