



MODEL	A	B	C	D	E
B-211F-ROHS (58U)	1.05	5.6	6.5	3.2	4.5
B-211G-ROHS (59U)	0.75/0.9	6.6	7.5	4.1	5.5
B-211A-ROHS (6U)	1.2	7.6	8.5	5.1	6.5

編號 ITEM NO.	ROHS		圖號 DRAWING NO.	ROHS		版次 EDITION	A 版
電鍍 PLATING	NGT		日期 DATE	2006 年 06 月 22 日		製圖 DRAWER	Elva
描述 DESCRIPTION	BNC STRAIGHT CRIMP JACK (RG-58.59.6) (75Ω)		單位 UNIT	mm	比例 SCALE	3.4:1	設計 DESIGN
	公差	0-0.5mm ± 0.10mm	0.5-8mm ± 0.20mm	8-30mm ± 0.40mm	30-120mm ± 0.50mm	認定 APPROVED	<i>[Signature]</i> 6/22

NO	DESCRIPTION	Q'TY	ITEM NO.	MATERIAL	PLATING
1	BODY 1	1	B-211F.G.A-ROHS	BRASS	NICKEL 100μ"MIN.
2	BODY 2	1	B-211-ROHS	BRASS	NICKEL 100μ"MIN.
3	DIELECTRIC	1	T-070015	TEFLON	-
4	CENTER PIN	1	T-241F.G.A-ROHS	BRASS	GOLD 3-5μ"MIN.
5	FERRULE	1	F-08.07.08001-ROHS	BRASS	NICKEL 100μ"MIN.

NGT: 1st N is Nickel for body. 2nd G is Gold for pin.
3rd T is Teflon for insulation.